

# C9370C

## brake lathe

- The lathe uses precision electric DC servo motors designed to meet the demanding requirement of industrial motion control.
- The "Change Adapter" system eliminates the need for conventional bell clamps and cones and features built-in springs ensure you don't lose them.
- The precision twin cutter tools and a quick drum to rotor changeover to help increase your service capability.
- Infinitely variable spindle and cross feed speed settings allow for quick rough and precision finish cuts.
- A convenient top storage tray means you can easy to take that are your favorite adapters and tools.
- Separate motors on the drum and rotor feed help maximize the main motor's efficiency.
- The variety of adapters lets you machine all standard and composite rotors for foreign and domestic cars and light trucks.
- Positive rake cutter tip angle provides for a one pass finish virtually every time, allowing you to complete your work fast.

### Technical Specifications

<b>Model</b>	<b>C9370C</b>
Spindle Travel	9.875"(251mm)
Rotor diameter	7"-18"(180mm-457mm)
Drum diameter	6"-28"(152mm-711mm)
Motor	110V/220V/380V,50/60HZ
Spindle speed	70,88,118 rpm
Rotor thickness	4"(102mm)
Drum depth	9.875"(251mm)
Shipping weight	350 kg
Dimension(L×W×H)	1100mm×1070mm×1140mm

### Optionnal adapter

1#(26 PCS)adaper kit for 1/2 ton

2#(28 PCS)adaper kit for 3/4 ton

3#(23 PCS)adaper kit for 1 ton



1#



2#



3#

